SKYHAWK

LEADING THE WAY





SKYHAWK



Scan to explore more.



A rugged yet sophisticated flight trainer, the Cessna® Skyhawk® piston still holds the world record for the longest continuous flight, and it's most likely the aircraft you first flew. This absolutely forgiving flying icon has been updated with new features and wireless connectivity to stay the course and become even more beloved.

TRAINING-FRIENDLY

Offering an optional three-seat crew training configuration, this high-wing piston allows for superior views, perfect to build skills. Newly added soundproofing and LED lighting for night training come standard. Two large loading doors make for easy boarding and deplaning.

PROVEN PROTECTION

Opt for digital autopilot equipped with Electronic Stability and Protection (ESP) and Underspeed Protection (USP).



FUTURE FORWARD FLIGHT DECK

The Garmin® G1000® NXi with enhanced graphics is perfectly suited to help gain experience and comfort in the cockpit. The Cessna® Skyhawk® piston's instrument panel now includes Garmin® GI 275 Electronic Standby and dual USB ports. Optional satellite-based weather graphics, text and voice bring you up to speed.



CONTACT YOUR TEXTRON AVIATION REPRESENTATIVE

U.S. +1.844.44.TXTAV | INTERNATIONAL +1.316.517.8270 | CESSNA.COM

© 2024 Textron Aviation Inc. All rights reserved. Cessna® & design and Skyhawk® are trademarks or service marks of Textron Aviation Inc. or an affiliate and may be registered in the United States or other jurisdictions. Garmin® and G1000® are trademarks and/or service marks of their respective owners.

DIMENSIONS

Wingspan	36 ft 1 in	11.00 m
Length	27 ft 2 in	8.28 m
Height	8 ft 11 in	2.72 m
WEIGHTS		
Max Takeoff Weight	2,550 lb	1,157 kg

1,680 lb

878 lb

762 kg

398 kg

POWERPLANT

Basic Empty Weight

Useful Load

Manufacturer		Lycoming	
Model	IO-360-L2A		
Power Output	180 hp	134 kW	

MAX OCCUPANTS

PERFORMANCE*

Max Cruise Speed	124 ktas	230 km/h
Max Range	640 nm	1,185 km
Takeoff Ground Roll	960 ft	293 m
Max Climb Rate	730 fpm	223 mpm

*Performance data is based on standard conditions with zero wind. Field performance assumes a level, hard-surface, dry runway. Range is based on a ferry mission with one pilot at 45% power with IFR reserves.